

PRODUCT NAME :	KANSAI PLC 55 RL
DESCRIPTION :	<i>KANSAI PLC 55 RL is a pigmented solvent-based acrylic marking paint formulated using proven methacrylate resins to provide long durability over concrete, cement render and asphalt surfaces for interior and exterior applications. It contains specially selected colour pigments to ensure good visibility in any weather condition. KANSAI PLC 55 RL is a high build coating and has very short drying time.</i>
RECOMMENDED USE :	<i>KANSAI PLC 55 RL is widely used for marking on either concrete or asphalt road surfaces. It is also recommended for marking of factories, warehouses and workshops floors.</i>
PERFORMANCE :	<ul style="list-style-type: none"> • <i>Adhesion - Excellent adhesion over concrete and asphalt surfaces.</i> • <i>Fast dry – dry in 15 minutes.</i> • <i>Excellent performance old, painted and new surfaces.</i> • <i>Can be applied by spray, roller or brush.</i> • <i>Easy application - simple mixing and application procedures.</i> • <i>Excellent weathering resistance for exterior applications.</i>
PHYSICAL PROPERTIES	
FINISH	<i>Matt</i>
COLOUR	<i>White, Yellow (Other colors available upon request)</i>
NO. OF COMPONENTS	<i>One</i>
VOLUME SOLIDS	<i>50 %</i>
RECOMMENDED THICKNESS	<i>100 microns DFT per coat</i>
TEORETICAL COVERAGE	<i>5m²/liter @ 100 microns DFT</i>
NO. OF COATS	<i>Two</i>
RECOMMENDED DRYING TIME	<i>Touch dry : 15 minutes</i> <i>Topcoat : 30 minutes</i> <i>Traffic : 1 hour</i>
PACKING SIZE	<i>5 liters</i>
SURFACE PREPARATION	<i>Remove loose dust, loose particles, oil and grease from the surface.</i>
MIXING	<i>Agitate with power stirrer or stick to mix the resin base and the pigments which might have.</i>

APPLICATION	<i>KANSAI PLC 55 RL can be applied by roller, brush or spray. For roller application, use only recommended thinner to ensure good workability.</i>
THINNING	<i>Can be thinned up to 10% with KANSAI PLC Thinner #715 for workability.</i>
DRYING	<i>Allow to cure for at least 30 minutes before re-coating.</i>
CLEANING	<i>Clean all tools and equipment with KANSAI PLC Cleaner #72 immediately after use.</i>

For further information on Product Data, please contact:

Protective Coatings Sales Department

Kansai Paint Asia Pacific Sdn Bhd. (705919-W)
4 Solok Waja 2, Kawasan Perindustrian Bukit Raja, P.O.BOX 159, 41710 Klang, Selangor, Malaysia
Tel: 6(03) 3362 2388 Fax: 6(03) 3342 7223

DISCLAIMER :

The information in this sheet is provided to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond the manufacturer's control, it is the sole responsibility of the buyer to obtain confirmation from the manufacturer on the suitability of the product for the intended use. Therefore, the manufacturer can accept no liability for the performance of the product, or any loss or damage arising out of such use. The information detailed in this data sheet is subject to change without notice in light of experience and of normal product development.