

PRODUCT NAME :	KANSAI PLC 65 CS
DESCRIPTION :	<i>KANSAI PLC 65 CS is a translucent white pigmented solvent-based sealer designed for usage as a tie-coat for chalked surfaces to accept new top-coats. It is formulated using special synthetic resins with outstanding surface wetting properties that penetrates the chalked surface to adhere to the sound substrate. It is also effective as a stain sealer against smoke and tannin stains on walls and plaster ceiling.</i>
RECOMMENDED USE :	<i>KANSAI PLC 65 CS is recommended for old interior and exterior walls where the old paint has chalked due to long exposure to ultra-violet radiation and weathering cycle. It is also used as a stain sealer on plaster ceiling to cover stains caused by water from leaking suffix.</i>
PERFORMANCE :	<ul style="list-style-type: none"> • <i>Excellent alkali resistance.</i> • <i>Effective stain sealer for ceiling and wall.</i> • <i>Adhesion - Excellent adhesion over chalked painted surfaces.</i> • <i>Easy application - simple application procedures.</i> • <i>Excellent weathering resistance for exterior applications.</i>
PHYSICAL PROPERTIES	
COLOUR	<i>Translucent white</i>
NO. OF COMPONENTS	<i>One</i>
VOLUME SOLIDS	<i>40 %</i>
RECOMMENDED THICKNESS	<i>50 microns DFT per coat</i>
TEORETICAL COVERAGE	<i>8m²/liter @ 50 microns DFT</i>
NO. OF COATS	<i>One</i>
RECOMMENDED DRYING TIME	<i>Touch dry : 45 minutes Topcoat : 5 hours</i>
PACKING SIZE	<i>20 liters</i>
SURFACE PREPARATION	<i>Surface to be coated must be dry and free form oil and grease.</i>
APPLICATION	<i>KANSAI PLC 65 CS can be applied by roller, brush or spray. For roller application, use KANSAI PLC THINNER #715 to ensure good workability.</i>
DRYING	<i>Allow to dry for at least 5 hours before top-coating.</i>
CLEANING	<i>Clean all tools and equipment with KANSAI PLC Cleaner #72 immediately after use.</i>

For further information on Product Data, please contact:

Protective Coatings Sales Department

Kansai Paint Asia Pacific Sdn Bhd. (705919-W)
4 Solok Waja 2, Kawasan Perindustrian Bukit Raja, P.O.BOX 159, 41710 Klang, Selangor, Malaysia
Tel: 6(03) 3362 2388 Fax: 6(03) 3342 7223

DISCLAIMER :

The information in this sheet is provided to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond the manufacturer's control, it is the sole responsibility of the buyer to obtain confirmation from the manufacturer on the suitability of the product for the intended use. Therefore, the manufacturer can accept no liability for the performance of the product, or any loss or damage arising out of such use. The information detailed in this data sheet is subject to change without notice in light of experience and of normal product development.